



Distributed by: CHAOS Moto

Phone: (480) 829-7888

Website: chaosmoto.com

Technical Data Sheet

Bubble Check Professional Tire Leak Detector

Product Description

CHAOS Moto **Bubble Check Professional Tire Leak Detector** rapidly identifies slow air leaks by instantly forming visible bubbles at the source. Engineered for professional tire and automotive service centers, Bubble Check eliminates guesswork and provides clear, visual proof of leaks, greatly reducing service turnaround times and enhancing customer satisfaction.

Features and Benefits

- Instantly detects even the smallest leaks in tires
- Clear, visual confirmation of leak locations
- Water-based, non-flammable formula for tire and shop-air checks
- Reduces diagnostic time and service callbacks
- No mixing required, ready-to-use
- Trusted by leading automotive and tire service providers

Directions for Use

1. Spray Bubble Check generously onto suspected leak areas.
2. Observe for rapid bubble formation, clearly indicating leaks.
3. Mark leak location, clean surface, and perform necessary repairs.
4. Wipe or rinse off remaining solution after repair.

Precautionary Information

- Wear eye protection and gloves during use.
- Use in well-ventilated areas; avoid inhalation of mist.
- Avoid prolonged skin contact.
- For eye contact, flush immediately with water and seek medical attention if irritation persists.
- Refer to the SDS for detailed safety guidelines.

Environmental and Disposal Information

- Dispose according to local, state, and federal regulations.
- Do not discharge directly into waterways.
- Containers should be recycled or disposed of responsibly.

Physical and Chemical Properties

Property	Value
Physical State	Liquid
Color	Clear, colorless
Odor	Mild
pH (at 25° C)	7.0 - 8.0 (neutral)
Flash Point	> 200°F (non-flammable)
Specific Gravity	~1.0 (8.33 lb/gal at 20°C)
Shelf Life	12 months from fill date
Storage Temperature	40°F - 90°F (4°C - 32°C)
Solubility	Completely soluble in water

Recommended Applications

- Tread, bead/rim, valve, TPMS, and post-repair leak checks
- Inner tubes
- Water-compatible shop air: hoses, couplers, fittings, tanks, tire machines
- Excluded: refrigerant, propane, natural gas, CSST, oxygen, nitrox

Regulatory Information

- SDS v1.0013, revised Aug. 4, 2026: H320, Causes eye irritation
- Not classified as a skin sensitizer under SDS v1.0013
- See SDS v1.0013 for DOT, TSCA, and SARA information
- Current preservative has no Prop 65 reporting requirement

Packaging and Ordering Information

- **Available Sizes:** 32 oz spray bottles (6 per case); 1-gallon refill jugs available
- **Ordering:** Contact CHAOS Moto at **(480) 829-7888** or visit chaosmoto.com.

